PACE 116 * RCVD AT 5/27/2004 10:56:50 PM [Eastern Daylight Time] * SYR: USPTO-EFXRF-111 * DNIS:8729306 * CSID:735/2326 * DURATION (mm-ss-10:456-116)

HENRY I. SCHANZER

Attorney At Law 29 Brookfall Road

Edison, New Jersey 08817

Telephone: (732) 572-3984 or (732) 572-9199

Fax: (732 572-3653

May 25, 2004

Fax: 703-305-772

RECEIVED CENTRAL FAX CENTER

MAY 2 7 2004

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant

Serial Number

For

Hoffman, G.

10/081,630

: APPARATUS AND METHOD FOR **TESTING BATTERY CONDITION**

Filed

: 02/21/02

Examiner Art Unit

: LUK, LAWRENCE.

: 2838

LETTER IN RESPONSE TO EXAMINER'S QUERY

The Examiner, Mr. Luk, just called my office with an indication that he had not received a response to the office action of 10/03/03 and that this note and a copy of the amendment should be faxed to the number indicated above...

Please be advised that the attached amendment was sent to the USPTO on 12/29/03.

As further evidence, attached is a copy of the postcard indicating receipt of our response by the by the USPTO on De. 31, 2003. Also enclosed are copies of the front and back of a check for \$9.00 which had been sent with the amendment and which was cashed by the USPTO.

I trust that this will clear up this matter. If there are nay questions please contact

Respectfully Submitted

Henry I. Schanzer

Reg. # 25,219

PLEASE CONFIRM RECEIPT OF THIS FAX.

May. 27 2004 09:58PM P1

FAX NO. : 7325723653

FROM : HSCHANZEREQ

PAGE 2/6 * RCVD AT 5/27/2004 10:56:50 PM [Eastern Daylight Time] * SYR: USPTO-EFXRF-1/1 * DNIS:8729306 * CSID:735723523 * DURATION (mm-ss):01-36

10/081, 630
APPARATUS & METHOD
FOR TESTING BATTERY
CONDITION-6-3
GARY HOFFMAN
AMENDMENT
Sq or Sor Additional
Claim



May. 27 2004 09:59PM P2

FAX NO. : 7325723653

FROM : HSCHANZERED

PAGE 316 * RCVD AT 512712004 10:56:50 PM [Eastern Daylight Time] * SYR: USPTO-EFXRF-111 * DNIS:8729306 * CSID:7325723653 * DURATION (mm-ss):01-36

HENRY I. SCHANZER ATTORNEY BUSINESS ACCOUNT 29 BROOKFALL ROAD EDISON, NJ 08817 (732) 572-3984 10/08/ 630 GB

55-216/212

2427

PAY WINE DOLLARS

DATE TO THE CHOER OF DESCRIPTION CHECK NO.

12/29/03 Commissioner for Patents & Tradensks 19/081,630 Amendment 6-3 2427

CHECK AMOUNT

9.00

SUMMIT S5 WOODBRIDGE AVENUE

#OD 24 27# #O 21 20 215 2#

932470631 24

May. 27 2004 09:59PM P3

FAX NO. : 7325723653

FROM: HSCHANZEREA

PAGE 4/6 * RCVD AT 5/27/2004 10:56:50 PM [Eastern Daylight Time] * SVR: USPTO-EFXRF-1/1 * DNIS:8729306 * CSID:7325723653 * DURATION (mm-ss):01-36

FLEET 110 1 08 010920 F1...

TENT AND TRADEMAR 13-10-0001 91-07-2004 FOR CREDIT-TO U.S. TRESSIR

03:19696-11 PROCESS TWA-BANK SWC-75 6 109769 HOUNTS HAVE HE SPECT

5224843066 <mark>7311</mark>639<u>208</u>

May. 27 2004 09:59PM Pa

FAX NO. : 7325723653

EROM: HSCHUNZEREd

PACE 516 * RCVD AT 512712004 10:56:50 PM [Eastern Daylight Time] * 54R:USPTO-EFXRF-111 * DNIS:8729306 * CSID:7325723653 * DURATION (mm-ss):01-36

Hoffman g-3-amendment

I hereby certify that this correspondence is being deposited with the United States Postal Service as First Class Mail in an envelope addressed to Commissioner for Patents, P.O. Box 1450, Alexandria VA 22313-1450

CENTRAL FAX CENTER

MAY 2 7 2004

OFFICIAL

s/n; 10/081,630

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant

: Hoffman, G.

Serial Number

10/081,630

For

: APPARATUS AND METHOD FOR TESTING BATTERY CONDITION

Filed

02/21/02

Examiner

: LUK, LAWRENCE.

Art Unit

: 2838

AMENDMENT

In response to the office action dated 10/03/03, please amend the above-identified application as follows:

PAGE 616 * RCVD AT 5127/2004 10:36:30 PM [Eastern Daylight Time] * 8VR:USPTO-EFXRP-1/1 * DNIS:8729306 * CSID:7325723653 * DURATION (mm-cs):07-36

circultry and wherein the microprocessor circultry is programmed to determine the value of the battery resistance.

- 5. (original) In the system as claimed in claim 1, wherein the battery is a first battery for supplying power to the load, with a load current from the first battery flowing through the load within a first loop; and wherein the current source generating a first current includes a second power source for supplying said first current and wherein said first current flows through a second loop which includes the first battery and said second power source.
- 6. (currently amended) In the system as claimed in claim 5, wherein the first battery and the second power source are connected in series, with the first battery and the second power source poled so their voltages are adding
- 7. (currently amended) In the system as claimed in claim 5, wherein the first battery and the second power source are connected in series, with the first battery and the second power source poled so their voltages are opposing.
- 8. (currently amended) in the system as claimed in claim 5, wherein the first battery, the second power source, the current source, the selectively enabled switch and the resistor are connected in series defining said second conductive loop for selectively passing said first current.

IN THE CLAIMS:

4 4, 1

- (currently amended) In a system in which a load is connected across first and second power terminals of a battery, a circuit for sensing the condition of the battery comprising:
 - · a current source generating a first current;
 - a resistor;
 - a selectively enabled current-switch,

means connecting the current source in series with the resistor, the selectively enabled eurrent switch, and the battery for selectively passing the first current through the resistor and the battery;

means for sensing the voltage across the resistor; and means for sensing the voltage across the battery for the condition when the selectively enabled switch is open and for the condition when the selectively enabled switch is closed.

- (original) In the system as claimed in claim 1, wherein the voltage is sensed across the resistor to determine the amplitude of the first current.
- 3. (original) In the system as claimed in claim 2, wherein the values of the voltages sensed across the battery when the selectively enabled switch is closed and then opened and the value of the voltage sensed across the resistor are for determining the value of the resistance of the battery.
- 4. (original) In the system as claimed in claim 1, wherein the voltage sensed across the resistor is coupled to microprocessor circuitry and wherein the voltage sensed across the battery is also coupled to the microprocessor.